

Safety Data Sheet

S446

Print date: June 24, 2016

Page 1 of 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product identifier**

HS 446, S446 Vinyl Polysiloxane Tray Adhesive

Relevant identified uses of the substance or mixture and uses advised against Vinyl Polysiloxane Tray Adhesive**Details of the supplier of the safety data sheet**

Company name: Parkell Inc.
 Street: 300 Executive Drive
 Place: Edgewood NY 11717
 Telephone: 631 2491134
 24 Hour Emergency: 1-800-5355053 (North America) INFOTRAC 1-352-323-3500 (International)
 Internet: www.parkell.com

SECTION 2: Hazards identification**Classification of the substance or mixture**

Indications of danger : Highly flammable, Harmful, Irritant, Dangerous for the environment

R-phrases:

Possible risk of impaired fertility.

Highly flammable.

Irritating to skin.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Vapours may cause drowsiness and dizziness.

GHS classification

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Reproductive toxicity: Repr. 2

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - repeated exposure: STOT RE 2

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

May cause drowsiness or dizziness.

Suspected of damaging the unborn child.

May cause damage to organs through prolonged or repeated exposure.

Toxic to aquatic life with long lasting effects.

Label elements**Hazardous components which must be listed on the label**

n-hexane

Signal word:

Danger

Pictograms:

GHS02-GHS07-GHS08-GHS09

**Hazard statements**

H225

Highly flammable liquid and vapour.

A00916rev*0716

Safety Data Sheet

according to Regulation (EC) No 1907/2006

S446

Page 2 of 7

H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Additional advice on labelling

Do not breathe vapour.

SECTION 3: Composition/information on ingredients

Mixtures

Chemical characterization

chemical characterization (preparation): Silicon, Petroleum distillate.

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
203-777-6	n-hexane	65 %
110-54-3	F, Repr. Cat. 3, Xn, Xi, N R11-62-48/20-65-38-67-51-53	
601-037-00-0	Flam. Liq. 2, Repr. 2, Asp. Tox. 1, STOT RE 2, Skin Irrit. 2, STOT SE 3, Aquatic Chronic 2; H225 H361f *** H304 H373 ** H315 H336 H411	

Full text of R- and H-phrases: see section 16.

SECTION 4: First aid measures

Description of first aid measures

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

After contact with skin, wash immediately with: Water and soap. Change contaminated clothing.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Immediately get medical attention.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media

Extinguishing powder. Sand. Foam. Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons

High power water jet.

Additional information

Highly flammable. Formation of potentially explosive mixtures with: Air.

SECTION 6: Accidental release measures

Safety Data Sheet

S446

Page 3 of 7

Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Keep away from sources of ignition - No smoking.

Environmental precautions

Do not empty into drains or the aquatic environment.

Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

SECTION 7: Handling and storage**Precautions for safe handling****Advice on safe handling**

Keep container tightly closed. Avoid contact with eyes. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Use explosion-protected machinery, apparatus, suction equipment, appliances etc.

Further information on handling

Wear suitable protective clothing and gloves.

Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.
Store only in original container.

SECTION 8: Exposure controls/personal protection**Control parameters****Exposure limits (EH40)**

CAS No	Chemical name	ml/m ³	mg/m ³	F/ml	Category	Origin
110-54-3	n-Hexane	20	72		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

Additional advice on limit values

exposure limit values: MAK: 50 ppm (n-hexane:: 20 ml/m³; 72 mg/m³)
Reproduction toxicity:

Exposure controls**Occupational exposure controls**

Ensure adequate ventilation of the storage area.

Protective and hygiene measures

When using do not eat or drink.

Respiratory protection

The following must be prevented: inhalation.

Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

Eye protection

Tightly sealed safety glasses.

Safety Data Sheet

S446

Page 4 of 7

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties**

Physical state: liquid
 Colour: blue
 Odour: characteristic

Test method

pH-Value: not applicable

Changes in the physical state

Boiling point: > 60 °C

point of decomposition:

Flash point: > -20 °C

Explosive properties

0,8 - 8,0 Vol. %

Ignition temperature: > 260 °C

Density: 0,8 g/cm³

Water solubility: insoluble

SECTION 10: Stability and reactivity**Conditions to avoid**

heat. Light. Remove all sources of ignition.

Hazardous decomposition products

Can be released in case of fire: Carbon monoxide.

SECTION 11: Toxicological information**Information on toxicological effects****Acute toxicity**

LD50: Rat. 2000 mg/kg

Irritation and corrosivity

Irritating to eyes, respiratory system and skin.

SECTION 12: Ecological information**Toxicity**

Preparation not tested.
 Harmful to aquatic organisms.

Persistence and degradability

Preparation not tested.

Further information

Do not empty into drains or the aquatic environment. Leakage into the environment must be prevented.

SECTION 13: Disposal considerations**Waste treatment methods****Advice on disposal**

Carry out a burning of hazardous waste according to official regulations.

Safety Data Sheet

S446

Page 5 of 7

Waste disposal number of waste from residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing dangerous substances
Classified as hazardous waste.

Waste disposal number of used product

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing dangerous substances
Classified as hazardous waste.

SECTION 14: Transport information**Land transport (ADR/RID)**

UN number: 1268
UN proper shipping name: PETROLEUM DISTILLATES, N.O.S.
Transport hazard class(es): 3
Packing group: II
 Hazard label: 3



Classification code: F1
 Special Provisions: 640D
 Limited quantity: 1 L
 Transport category: 2
 Hazard No: 33
 Tunnel restriction code: D/E

Other applicable information (land transport)

E2

Marine transport

UN number: 1268
UN proper shipping name: PETROLEUM DISTLLATES, N.O.S.
Transport hazard class(es): 3
Packing group: II
 Hazard label: 3



Special Provisions: -
 Limited quantity: 1 L
 EmS: F-E, S-E

Other applicable information (marine transport)

E2

Air transport

UN/ID number: 1268

Safety Data Sheet

S446

Page 6 of 7

UN proper shipping name: PETROLEUM DISTLLATES, N.O.S.
Transport hazard class(es): 3
Packing group: II
 Hazard label: 3



Limited quantity Passenger: 1 L
 IATA-packing instructions - Passenger: 353
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 364
 IATA-max. quantity - Cargo: 60 L

Other applicable information (air transport)

E2
 : Y341

Environmental hazards

Dangerous for the environment: yes

**SECTION 15: Regulatory information****Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulatory information**

Water contaminating class (D): 1 - slightly water contaminating

SECTION 16: Other information**Full text of R-phrases referred to under sections 2 and 3**

11 Highly flammable.
 38 Irritating to skin.
 48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 51 Toxic to aquatic organisms.
 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 53 May cause long-term adverse effects in the aquatic environment.
 62 Possible risk of impaired fertility.
 65 Harmful: may cause lung damage if swallowed.
 67 Vapours may cause drowsiness and dizziness.

Full text of H-Statements referred to under sections 2 and 3

H225 Highly flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H361d Suspected of damaging the unborn child.
 H361f Suspected of damaging fertility.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H411 Toxic to aquatic life with long lasting effects.

Further Information

-

Safety Data Sheet

S446

Page 7 of 7

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)
